

WaterGroup®

185 TAN Series

This system uses Anion exchange resin to remove color caused by organic decay - greatly improving aesthetics and preventing costly staining.



Specifications	WG185DFTAN-100	WG185DFTAN-150	WG185DFTAN-200	WG185DFTAN-300*
Purolite 850 Models*	2229-850	2143-850	2144-850	2145-850
Purolite 860 Models*	2230-860	2146-860	2147-860	2148-860
Factory Settings - High Capacity				
Salt Used - Per Regeneration	12.0 lbs	18.0 lbs	24.0 lbs	36.0 lbs
Water Used - Regeneration	64.3 US gal	90.3 US gal	124.6 US gal	196.2 US gal
Tannins Removal	2000 ppm	3000 ppm	4000 ppm	6000 ppm
Resin Quantity - Cubic Feet	1.0 ft	1.5 ft	2.0 ft	3.0 ft
Tank Size	9x48	10x54	12x52	14x65
Tank Jacket / Media Loaded	Yes	Yes	No	No
Brine Tank / Cabinet Size (Inches)	18.1 x 34.5	20.3 x 37.4	20.3 x 37.4	23.0 x 40.5
Salt Storage Capacity	240 lbs	350 lbs	350 lbs	420 lbs
Recommended Service Flow Rate	3.0 gpm	4.5 gpm	6.0 gpm	9.0 gpm
Flow Rate @ 15 psi Pressure Drop	11.0 gpm	11.2 gpm	12.2 gpm	12.6 gpm
Flow Rate @ 25 psi Pressure Drop	15.0 gpm	15.1 gpm	16.2 gpm	16.6 gpm
Back Wash Flow Rate	1.5 gpm	2.0 gpm	3.0 gpm	4.0 gpm
Shipping Weight	122 lbs	155 lbs	158 lbs	244 lbs
Regeneration Type	Co-Current / Down Flow			
Maximum Tannins	3.0 ppm (Contact Customer Service for higher levels)			
Plumbing Connections	Includes 3/4" 90° Elbows & 1" Straight NPT			
Resin Type	Canature Anion Resin			
Electrical Requirements	Input 120V 60 Hz - Output 12V 550mA			
Water Pressure	Min. 20 - Max. 125 psi			

*Media not loaded in mineral tank.



WaterGroup®

Toll Free: 1-877-288-9888
www.watergroup.com

Regina, SK • Cambridge, ON • Whitestown, IN
 Houston, TX • Phoenix, AZ • Guadalajara, MX

Your Local Plumbing Professional